

Centrifugal Barrel Finishing Machine

HS8V-10G ***Vertical***



HS8V-10G



Easy·Safe·Robust

The definitive edition for polishing small parts!

Patent

US3233372 JP4189010

Made in Japan

Compact and Easy-to-handle Centrifugal Barrel Polishing Machine Vertical Type

Application

- ▶ Electronics
- ▶ Semiconductor
- ▶ Precious metal
- ▶ Machine parts
- ▶ Medical • Dentistry
- ▶ Daily necessities

From deburring to mirror finish

Benefit

Easy operation

Long life

Lightweight
Safety

Chipping
reduction

Renewal from Best-Selling HS-2-4VII

HS-2-4V II



Easy installation of barrel tank

NEW

1 Set the barrel tank in the case



2 Lock automatically by turning the cross stopper 4 tanks fixed simultaneously by spring force

*Bolt fixing of the stopper has been eliminated, making it easier to use since HS-2-4VII.



Patent | JP4189010

Sliding door

NEW




A robust door withstands accidental barrel tank drop.

In combination with the safety door switch, it ensures safety. The sliding type reduces the risk of hands being pinched, unlike conventional vertical doors, and allows safe operation.

Rotation speed feedback function

NEW

If there is a difference from the set number of revolutions, automatic correction is applied to maintain the polishing quality.



Standard touch panel


NEW

The multi-stage operation setting allows for a wider range of polishing.



Easy for women to handle lightweight barrel tank

This barrel tank is a lightweight model made of all urethane. Even female operators can easily carry and load it. Help you work faster and more efficiently.



Solid lid tightening suppresses liquid leakage. The inside of the cabin is hard to get dirty with polishing liquid and prevents damage.




Keyhole slot


When opening the barrel lid, simply loosen the nut through the keyhole slot!

Options

Round barrel tank and sticking prevention tank (dimple type) are also available as options.



Round Shaped Tubs




Tubs with Dimpled Surface Urethane Lining

Spec.

Model	HS8V-10G
Relative centrifugal acceleration	10G
Barrel capacity	2L × 4 tubs
ID of Barrel Tub	135mm(Diagonal line) × 130mm(Depth)
Motor capacity	1.5kW
Machine size	760mm(W) × 760mm(D) × 1660mm(H)
Machine weight	Approx.340kg *Not including barrel tank

Dimension (mm)



Tipton Corp.

Head Office	3-19-21 Toyoda, Minami-Ku, Nagoya, Aichi Prefecture 457-8566 Japan Tel : +81-52-692-6666 Fax : +81-52-692-9445
Headquarter-Sales	3-19-21 Toyoda, Minami-Ku, Nagoya, Aichi Prefecture 457-8566 Japan Tel : +81-52-692-7175 Fax : +81-52-692-0249
Tobishima Factory	3-25-1 Odakara, Tobishima-Mura, Ama-Gun, Aichi Prefecture 490-1438 Japan Tel : +81-567-56-7500 Fax : +81-567-56-7513
Tipton USA Inc.	2450 W Broadway Rd. Suite 108, Mesa, AZ 85202, USA Tel : +1-480-795-2647

Quality Assurance Section for Product Quality

Tel : +81-567-56-7503 Fax : +81-567-56-7516

Engineering Section for Machine Maintenance

Tel : +81-567-56-7504 Fax : +81-567-56-7514

Web Site

<https://www.tipton.co.jp>



Download
Catalog



E-mail

sales-department@tipton.co.jp
sales-department@tiptonusa.com (North America)

HS8V-10G

Product Information



Products



YouTube



Access our social media for more!